Common Problems in Welded Manifolds

Typical Issues, Causes, and How to Avoid Them

Welded manifolds are widely used in booster systems and industrial pumping applications. While they offer flexibility and cost-effective manufacturing, improper design or fabrication can lead to performance issues, increased maintenance requirements, and reduced system reliability. Although manifolds are often considered simple piping components, their design has a direct impact on hydraulic performance, flow distribution, energy consumption, and long-term operations.

Analysis of 6 Common Welded Manifold Issues

Typical Issue	Root Causes	Potential Effects & Prevention
1. Internal Weld Protrusion	• Poor welding control • Excessive heat input • Improper branch preparation • Inconsistent procedures	Effects: Flow obstruction, turbulence, pressure loss. Prevention: Controlled welding, joint preparation, qualified personnel.
2. Poor Branch Alignment	• Inaccurate fabrication • Improper fixturing during welding • Dimensional inconsistencies	Effects: Localized turbulence, uneven flow patterns, pump imbalance. Prevention: Precision fixtures, pre-weld inspection.
3. Inadequate Branch Spacing	• Compact layout requirements • Lack of hydraulic consideration • Space limitations	Effects: Flow interference between branches, uneven pressure distribution. Prevention: Proper layout design, flow analysis, reviews.
4. Excessive Pressure Loss	• Sharp internal transitions • Internal weld obstructions • Sizing errors / poor design	Effects: Higher pump head requirements, increased energy cost. Prevention: Hydraulic calculations, optimized manifold geometry.

Copyright © YURONG All rights reserved.

5. Corrosion & Contamination	• Incomplete cleaning • Lack of pickling and passivation • Surface contamination / improper handling	Effects: Surface corrosion, shortened life, poor appearance. Prevention: Pickling & passivation, controlled stainless handling.
6. Inconsistent Quality	• Lack of standard procedures • Insufficient quality control • Variable fabrication tolerances	Effects: Performance variations, install difficulties, low confidence. Prevention: Standardized production, pressure tests, strict QA.

Advanced Manufacturing Solution: Pull-Out Forming Technology

At YuRong Manifolds, our Pull-Out Forming Technology was developed specifically to minimize many of the challenges Commonly associated with traditional welded branch construction. Unlike conventional welded branches that may create internal weld protrusions and flow disturbances, the pull-out forming process creates a smooth transition between the header and branch connection. This allows fluid to move through the manifold with less disruption, significantly improving hydraulic performance.

Key Advantages of Pull-Out Forming:

- Smoother internal flow path & reduced turbulence at branch connections
- Lower overall pressure loss & improved fluid flow distribution
- Consistent manufacturing quality with enhanced structural integrity
- Elimination of internal weld obstruction risks
- Improved hydraulic operating efficiency for the booster system
- Longer service life with substantially lower maintenance requirements

Conclusion

For booster system manufacturers, every component influences overall system performance. While pumps, controls, and motors often receive the most attention, manifold design plays an equally important role in achieving efficient, reliable operation. By combining sound hydraulic principles with advanced manufacturing methods, Pull-Out Forming Technology helps create manifolds that support higher efficiency, better flow characteristics, and long-term system reliability.

Copyright © YURONG All rights reserved.