Conventional Welded vs Pull-Out Technology

Understanding the Difference in Booster System Manifold Design

The manifold plays a critical role in the hydraulic performance of any booster system. While many manifolds may appear similar externally, the manufacturing method used to connect branch pipes can significantly influence internal flow characteristics, pressure loss, long-term reliability, and overall system efficiency. Understanding the differences helps engineers select the most appropriate solution for demanding booster system applications.

Traditional Welded Construction	Pull-Out Technology
• Openings are drilled into the main header pipe • Branch connections are welded directly onto the surface • Internal geometry creates abrupt flow transitions • Creates sudden internal flow interruption • Internal weld protrusions & localized turbulence zones • Flow separation near branch connections • Higher hydraulic and energy losses	• Material of the main pipe is mechanically formed outward to create an integrated collar • Branch pipe is connected using a precision butt-weld configuration • Creates a smoother internal transition between header and branch • Improved flow continuity and reduced flow separation • Lower turbulence generation & more uniform velocity distribution • Consistent manufacturing quality

Key Performance & Engineering Impacts

Engineering Parameter	Detailed Impact
Turbulence & Flow Behavior	Turbulence is a primary source of energy loss. Traditional welded branches generate local vortices and recirculation zones around the weld area, causing hydraulic noise and vibration. Pull-Out Technology minimizes these effects for stable flow.
Pressure Loss	Every pressure loss must be compensated by pump power. Even small inefficiencies become significant over years. Manifolds with excessive turbulence require additional

Copyright © YURONG All rights reserved.

	energy, whereas optimized flow paths maximize operating efficiency.
Flow Distribution	In multi-pump systems, balanced flow distribution is essential. Uneven hydraulic conditions lead to unequal pump loading, increased wear on specific pumps, reduced operating stability, and shortened equipment life.
Long-Term Reliability	Hydraulic performance directly affects mechanical reliability. Lower turbulence and smoother flow conditions help reduce seal wear, bearing stress, vibration levels, and fatigue loading on pipework.

Conclusion

Both manufacturing methods can produce functional manifolds. However, the internal geometry created by Pull-Out Technology offers measurable hydraulic advantages in booster system applications. By improving flow continuity, reducing turbulence, and minimizing pressure loss, Pull-Out Technology helps engineers achieve higher efficiency, more stable operation, and improved long-term reliability.

Copyright © YURONG All rights reserved.